



SAILUN

RETREAD SPECIFICATIONS

SIZE	PATTERN	BUFFED CROWN RADIUS		BUFFED CROWN WIDTH		RIM WIDTH	
		mm	in	mm	in	in	
11R22.5	S605	510.0	20.079	222.6	8.764	8.25	
11R24.5		535.0	21.063	222.7	8.768	8.25	
295/75R22.5		493.0	19.409	221.3	8.713	9.00	
285/75R24.5		510.5	20.098	223.3	8.791	8.25	
11R22.5	S606	510.0	20.079	222.8	8.772	8.25	
11R24.5		535.0	21.063	222.9	8.776	8.25	
12R22.5		527.5	20.768	233.8	9.205	8.25	
295/75R22.5		493.0	19.409	221.1	8.705	9.00	
295/80R22.5		625.0	24.606	220.0	8.661	9.00	
285/75R24.5		510.5	20.098	223.5	8.799	8.25	
315/80R22.5	S665	648.5	25.531	246.0	9.685	9.00	
11R22.5		580.0	22.835	220.0	8.661	8.25	
11R24.5		580.0	22.835	220.0	8.661	8.25	
295/75R22.5		600.0	23.622	220.0	8.661	9.00	
285/75R24.5	S698	420.0	16.535	225.0	8.858	8.25	
315/80R22.5		680.0	26.772	245.0	9.646	9.00	
215/75R17.5	S637	372.5	14.665	163.0	6.417	6.00	
235/75R17.5		387.0	15.236	181.3	7.138	6.75	
225/70R19.5		393.5	15.492	182.9	7.201	6.75	
245/70R17.5		407.0	16.024	203.8	8.024	6.75	
245/70R19.5		407.0	16.024	203.8	8.024	7.50	
265/70R19.5		590.0	23.228	200.0	7.874	7.50	
255/70R22.5		452.5	17.815	204.8	8.063	7.50	
275/70R22.5		580.0	22.835	230.0	9.055	7.50	
9R22.5		522.0	20.551	185.0	7.283	6.75	
10R22.5		452.5	17.815	204.8	8.063	7.50	
11R22.5	S668	840.0	33.071	225.0	8.858	8.25	
11R24.5		840.0	33.071	225.0	8.858	8.25	
255/70R22.5		434.0	17.087	215.0	8.465	7.50	
295/75R22.5		664.0	26.142	225.0	8.858	9.00	
11R22.5	S622	513.0	20.197	205.8	8.102	8.25	
11R24.5		534.5	21.043	222.4	8.756	8.25	
255/70R22.5		575.0	22.638	205.0	8.071	7.50	
295/75R22.5		492.5	19.390	221.5	8.720	9.00	
285/75R24.5	S696	510.0	20.079	223.0	8.780	8.25	
445/50R22.5		1220.0	48.031	400.0	15.748	14.00	
11R22.5	S768	510.0	20.079	220.8	8.693	8.25	
11R24.5		535.0	21.063	220.9	8.697	8.25	
295/75R22.5		492.5	19.390	220.6	8.685	9.00	
285/75R24.5		510.0	20.079	219.9	8.657	8.25	
11R22.5	S757	925.0	36.417	240.0	9.449	8.25	
11R24.5		925.0	36.417	240.0	9.449	8.25	
295/75R22.5	S753	675.0	26.575	245.0	9.646	9.00	
10R22.5		452.5	17.815	204.8	8.063	7.50	
11R22.5		510.0	20.079	220.8	8.693	8.25	
11R24.5		535.0	21.063	220.9	8.697	8.25	
255/70R22.5		452.5	17.815	204.8	8.063	7.50	
295/75R22.5		492.5	19.390	220.6	8.685	9.00	
285/75R24.5		510.0	20.079	219.9	8.657	8.25	
11R22.5		SW01	875.0	34.449	230.0	9.055	8.25
11R24.5			875.0	34.449	230.0	9.055	8.25
225/70R19.5		S740	355.0	13.976	190.0	7.480	6.75
245/70R19.5	355.0		13.976	200.0	7.874	7.50	
215/75R17.5	S737	487.0	19.173	156.0	6.142	6.00	
225/70R19.5		393.5	15.492	183.3	7.217	6.75	
245/70R19.5		407.0	16.024	204.4	8.047	7.50	
315/80R22.5		654.5	25.768	246.0	9.685	9.00	
12R22.5	S811	527.5	20.768	243.1	9.571	9.00	
9.00R20		535.0	21.063	195.0	7.677	7.00	
10.00R20		580.0	22.835	220.0	8.661	7.50	
11.00R20		640.0	25.197	223.0	8.780	8.00	
12.00R20		680.0	26.772	240.0	9.449	8.50	
11R22.5		S815	510.0	20.079	220.5	8.681	8.25
11R24.5	535.4		21.079	220.5	8.681	8.25	
11.00R20	640.0		25.197	225.0	8.858	8.00	
12R22.5	654.9		25.787	230.0	9.055	9.00	
275/70R22.5	560.5		22.933	235.0	9.055	9.00	
315/80R22.5	650.0		25.591	230.0	9.055	9.00	
385/65R22.5	S825	770.0	30.315	315.0	12.402	11.75	
425/65R22.5		729.0	28.701	333.0	13.110	12.25	
445/65R22.5		768.0	30.236	351.0	13.819	13.00	
10.00R20	S911	580.0	22.835	216.0	8.504	7.50	
11.00R20		615.0	24.213	230.0	9.055	8.00	
11R22.5	S758	512.0	20.157	221.7	8.728	8.25	
11R24.5		537.0	21.142	221.8	8.732	8.25	
11R22.5	S917	610.0	24.016	224.0	8.819	8.25	
12R22.5		620.0	24.409	242.0	9.528	9.00	
11R24.5		610.0	24.016	224.0	8.819	8.25	
12.00R24		690.0	27.165	245.0	9.646	8.50	

Every effort has been made to verify the accuracy of the listed specifications. TBC Corporation and TBC Brands cannot be held responsible for any discrepancies, and as such, the information should be considered as approximate.

